

“Highly Versatile”

The **OTW VersaHone Vertical** honing machines provide the flexibility, value, and ease of use ideal for those who process a broad range of parts.

[Standard Features]

- Programmable Automatic Tool Expansion System
- Precision Handwheel Control
- Profile Linear Ways
- Touchscreen PLC Operator Controls
- Part Program Storage
- Full Servo Control
- Ball Screw Reciprocation

[Options]

- IIoT Ready w/ Full Data Capability
- Remote Connectivity for Online Support and Monitoring
- Single or Multi-Spindle Configurations
- Universal Fixture or Indexing Table
- Coolant Filtration System



Capacities/Technical Specifications

[OTW- VersaHone Vertical]

I.D. Capacity 0.25" – 6.0" (6.35 - 152 mm)

O.D. Capacity 8.0" (200 mm)

Stroke Capacities
12.0" (305 mm)
24.0" (610 mm)
36.0" (915 mm)

Stroke Power 5.5 kW

Spindle Drive Up to 10 kW *

Spindle Speeds Packages from 10 - 3500 RPM
Infinitely Variable

Stroke Rate 5-90 FPM
(1,5-27,4 M/MIN)
Infinitely Variable

Electrical System 480V / 3PH / 60 Hz **

Turnkey Solutions

Please ask about OTW's complete line of tooling, abrasives & consumables.



* Subject to specific application bore condition and base capacity ** Additional voltages available



Innungstraße 32
50354 Hürth-Gleuel

Telefon: 02233 / 39220
Telefax: 02233 / 392241
Internet: www.nepa.de
E-mail: info@nepa.de